Accessible Parking Checklist FOR BUSINESSES & PUBLIC SPACES

Number of Required Spaces for a Parking Lot

- 1-25 TOTAL SPACES REQUIRES 1 ACCESSIBLE SPACE
- 26-50 TOTAL SPACES REQUIRES 2 ACCESSIBLE SPACES
- 1 IN 6 ACCESSIBLE SPACES SHOULD BE VAN ACCESSIBLE

Dimensions & Access Aisles

- STANDARD ACCESSIBLE SPACE: 96" WIDE WITH 60" ACCESS AISLE
- VAN-ACCESSIBLE SPACE: 132" SPACE WITH 60" AISLE OR 96" SPACE WITH 96" AISLE
- ACCESS AISLES ARE LEVEL AND SAME LENGTH AS THE SPACE



Markings & Paints

- ALL ACCESS AISLES ARE CLEARLY STRIPED
- "NO PARKING" IS PAINTED IN ACCESS REQUIRED
- PAVEMENT MARKINGS ARE VISIBLE AND MAINTAINED

Location & Route

- ACCESSIBLE SPACES ARE LOCATED ON THE SHORTEST ACCESSIBLE ROUTE TO THE ENTRANCE
- ROUTES FROM PARKING TO ENTRANCE ARE FREE OF STEPS, BURBS, AND OBSTRUCTIONS
- NO BARRIERS OR LANDSCAPING BLOCK ACCESS AISLES OR ROUTES

Signage

- EACH ACCESSIBLE SPACE HAS A PERMANENT SIGN WITH ISA SYMBOL
- VAN-ACCESSIBLE SPACES INCLUDE "VAN ACCESSIBLE"
 ON THE SIGN
- SIGNS ARE MOUNTED AT LEAST 60" ABOVE GROUND TO ENSURE VISABILITY
- SIGNS AND MARKINGS ARE NOT FADED OR OBSTRUCTED